

Powercity GENERATORS

Model: PDG500S

500 KVA / 3 - Phase



Powercity generators are designed in conformance with European Standards certified by independent certifying agency the Materials Industrial Research and Technology Center (MIRTEC) with certificate number MC/TH-C-269/08. The principles in design, safety, rating and performance are in accordance with European Standards EN 12601:2001, EN 60204-1:2006, EN 60034-1:2004, EN ISO 12100-1:2003 and EN ISO 12100-2:2003. Generators are designed and built to provide electrical power for stand-by or continuous use. Comes with 2 years or 2,000 run hours limited warranty whichever comes first.

Features:


- MANUAL or AUTOMATIC starting and stopping capability.
- Digital controller.
- Direct injection diesel engine for fuel efficiency.
- Brushless rotating field generator with class H insulation.
- NEMA 3R enclosure suitable for outdoor use.
- Integral vibration isolators.
- Silent type generator.

Specifications

Model	PDG500S		
Alternator			
Make & Model	Powercity SLG-544C		
Frequency	Hz	50	60
Output Rating (KVA)	Prime	450	512
	Standby	500	560
Phase	3-Phase (4 Wires)		
Rated Voltage	V	200-240 / 380-440	
Power Factor	0.8 (Lagging)		
Voltage Regulation	%	Within +/- 1.5	
Excitation	Brushless rotating exciter with Automatic Voltage Regulator (AVR)		
Insulation	Class H		
Engine			
Make & Model	CUMMINS KTA19-G3		
Type	Vertical inline; water cooled; 4 stroke; direct injected; turbo-intercooled		
Output Rating	Kw/rpm	403/1500	463/1800
No. of cylinders-Bore X Stroke	mm	6 – 159 X 159	
Piston Displacement	L	18.9	
Fuel	ASTM No. 2 Diesel		
Fuel Consumption @ 75% Load	L/h	73	87
Lube Oil Capacity	L	50	
Coolant Capacity	L	106	
Battery Capacity	V-Ah	12V-150Ah (2 pcs)	
Fuel Tank Capacity	L	490	
Unit			
Dimensions	Length mm	4600	
	Width mm	1600	
	Height mm	2200	
Dry Weight	Kg	5500	
Sound Level			
dB @ 7 m		72	78

Note: Due to continuous product improvement, the generator set manufacturer reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever.

Engine:



G-Drive Generator Engines

Diesel engines with unrivalled reputation for reliability in generator industry!

Standards:

EN 12601:2001 – Reciprocating internal combustion engine driven generating sets – Safety.

EN 60204-1:2006 – Safety of machinery; electrical equipment of machines – General requirements.

EN 60034-1:2004 – Rotating electrical machines – Rating and performance.

EN ISO 12100-1:2003 – Safety of machinery; basic concepts and general principles for design Part 1.

EN ISO 12100-2:2003 – Safety of machinery; basic concepts and general principles for design Part 2.

Applicable EGSA* Standards.

*- Electrical Generating Systems Association

Application Notes:

STANDBY RATING: Standby ratings apply to installations served by a reliable utility source. This rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Ratings are in accordance with ISO 3046-1, BS 5514, AS 2789 and DIN 6271.

PRIME POWER RATING: Prime power ratings apply to installations where utility power is unavailable or unreliable. At varying load the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve hours. Ratings in accordance with ISO 8528-1, overload power in accordance with ISO 3046-1, BS 5514, AS 2789, and DIN 6271.

GENERAL GUIDELINES FOR DERATION:


Altitude: Derate 0.5% per 100 meter (328 ft.) elevation above 1000 meter (3279 ft.).

Temperature: Derate 1.0% per 10°C (18°F) temperature above 40°C (104°F).

FUEL: Use clean diesel fuel only. Diesel fuel quality should meet the specifications of ASTM D975 and the Worldwide Fuel Charter.

SOUND LEVEL: Sound level is measured in free field environment (acoustic test chamber) where sound may propagate free from any form of obstruction.

dB Range:



Quality Assurance:



ISO 9001:2008

Certificate No. U13Q2GZ682452F1M

Manufactured by:

Powercity Electromechanical & Equipment Co Ltd
Fujian, China

Distributed in the Philippines by:

Powercity Corporation
Km. 20, East Service Road, Muntinlupa City
Metro Manila, Philippines
Tel. (+632) 869 1991, (+632) 8697520
Fax. (+632) 8693869
Email: contactus@powercity.ph

Made in China